

2450

BOLTARON

2450 Super Clear

GENERAL INFORMATION

The newest generation of TruPrint Super Clear core stock is a near water clear PVC core material when planished. It has excellent impact resistance and die-cutting characteristics. Print surfaces can be customized to fit your printing needs. TruPrint Super Clear can be laminated to most allother TruPrint compounds giving printers added design capability .

Super clear is available in custom tints and gauges.

AVAILABILITY

Standard Gauges (.005" -- .030")

Sizes - Sheets custom cut to specifications

SUGGESTED APPLICATIONS

Credit Cards
Loyalty Cards
Phone Cards
Fare Cards
P.O.P. Displays
Labels
I.D.Tags
Promotional Items

Typical Physical Properties

Property	Test Method	Typical values
Specific gravity	ASTM D-792	1.30
Tensile strength (PSI)	ASTM D-638	6,100
Tensile modulus (PSI)	ASTM D-638	3.4×10^5
Flexural strength (PSI)	ASTM D-790	8,100
Flexural modulus (PSI)	ASTM D-790	3×10^5
Izod impact (Ft. lbs./in. of notch)	ASTM D-256	12
Hardness Rockwell R	ASTM D-785	104
Heat Deflection (°F) 264 PSI (annealed)	ASTM D-648	140
Vicat Softening point (°C)	ASTM D-1525	80 ±2

LIMITATION OF WARRANTY

The application suggestions, specifications and other data described here are based upon experience and information that is believed, by BPP to be reliable. However, BPP makes no express or implied warranty that BOLTARON 2024 will perform in accordance with such specifications in any particular circumstance. Therefore, ALL EXPRESS OR IMPLIED WARRANTIES IN CONNECTION WITH BOLTARON 2024, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY DISCLAIMED. The prospective user should determine the suitability of BOLTARON 2024 and the application suggestions before actual application.

One General Street, Newcomerstown, OH 43832

P 800.342.7444 **F** 740.498.5448 **E** info@boltaron.com

www.boltaron.com